

PEELABLE LIQUID PRIMER SYSTEM

LIQVIX PPS

Spray it. Protect it. Peel it.

LIQVIX PPS is a peelable liquid paint protection system. Sprayed on like paint and cured into a single seamless layer, it shields the factory finish from everyday damage. It can be tinted with custom color, loaded with powder pearls, metallic or holographic pigment, and finished in gloss or matte — then peeled away cleanly whenever a completely new look is wanted.



1 US GALLON (3.78 L)

■ TECHNICAL SPECIFICATIONS

PRODUCT TYPE	Peelable liquid paint protection
FINISH	Gloss / Matte
PIGMENT COMPATIBILITY	Color · Pearl · Metallic flake · Holographic
DRY FILM BUILD	180–220 microns
APPLICATION METHOD	HVLP spray
CURE TIME	24 hours
COVERAGE	Approx. 1 vehicle per 5 gallons
PACK SIZE	1 US gallon (3.78 L)
REMOVAL	Fully reversible — peels away cleanly
WARRANTY	10 years (professional application)

■ KEY FEATURES

Seamless coverage

Sprayed as a liquid, it reaches every curve, edge and recess in one continuous layer — no templates, cut lines or lifted edges.

Any color, any finish

Tint the primer, load it with pearl, flake or holographic pigment, and cure it gloss or matte.

Peel to reset

When a new look is wanted, the cured layer peels away cleanly and leaves the factory paint untouched.

■ APPLICATION PROCEDURE

1 Surface preparation

Wash, decontaminate and dry the vehicle thoroughly. The surface must be free of wax, sealants, oils and dust before application.

2 Masking

Mask glass, trim, lights, badges and any areas not to be coated.

3 Application

Apply with HVLP spray equipment in even, overlapping passes to build a uniform film of 180–220 microns. Add tint or pigment before spraying for custom finishes.

4 Cure

Allow 24 hours to cure. Gloss or matte is set at cure. A full vehicle is typically completed in a single session.

5 Removal

Lift an edge and peel the cured layer away slowly at a low angle. It releases cleanly without damaging the factory paint beneath.

■ FINISH OPTIONS

Custom Color

Tinted to any color before spraying — factory-match or bespoke.

Metallic Flake

True metallic flake blended in for a sparkling metal finish.

Gloss or Matte

The same finish dialed from deep wet gloss to flat matte at cure.

Powder Pearls

Pearl and mica pigment suspended in the liquid for depth and shift.

Holographic

Holographic pigment for a fully iridescent, color-shifting surface.

Clear

Untinted protection that deepens the paint underneath.

■ PROTECTS AGAINST

- Stone chips and road debris
- UV fading
- Chemical and environmental staining
- Light abrasion and wash marring

■ WARRANTY

Professionally applied LIQVIX PPS is backed by a 10-year warranty covering finish integrity and protective performance. Real-world longevity varies with climate, use and care.

■ STORAGE & HANDLING

- Keep container tightly sealed when not in use.
- Store in a cool, dry, well-ventilated area away from direct sunlight and ignition sources.
- Protect from freezing. Stir thoroughly before use.
- Use appropriate PPE including a respirator, gloves and eye protection during spray application.
- Refer to the Safety Data Sheet (SDS) for full handling and safety information.

The information in this data sheet is based on our current knowledge and is provided in good faith as a guide. Results depend on surface condition, preparation, equipment, environment and applicator technique, which are beyond our control. Users should confirm suitability for their specific application by testing on a small area first. Specifications are subject to change without notice.